

Submersible Drainage Pump

This submersible pump is suitable for draining clean water without abrasive particles. It is recommended for emergency draining of small flooded areas, for the disposal of non-sewage waste water in the home and for emptying drainage traps.



Product Overview

Submersible Drainage Pump

This submersible drainage pump is designed for efficient water removal in residential and light commercial settings. It features a robust construction with a technopolymer body and stainless steel components, ensuring durability and safe operation. Engineered for clean water applications, it is ideal for emergency draining of flooded areas or managing non-sewage wastewater.

Operating Limits

Max Immersion Depth	3 m
Max Liquid Temperature	40
Max Suspended Solids	10 mm
Suction Level	14 mm

Performance

Key Performance Metrics

130 l/min

Max Flow Rate

7 m

Max Head

Electrical Specifications

Protection Class

IP 68 • Class F Insulation

Power Supply

220-240V / 50Hz

Materials & Construction

Material Specifications

Component	Material
Pump Discharge Body	Glassfibre filled technopolymer
Suction Grid	Technopolymer
Impeller	Technopolymer (open type)
Motor Frame	Stainless Steel AISI 304
Motor Shaft	Stainless Steel AISI 420

Features

Key Features

- Double seal design with oil barrier chamber
- Thermal overload protector built into winding
- Continuous duty motor
- Float switch option available (Type F)