


# Submersible Water Transfer Pump

This submersible pump is designed for efficient water transfer. It is suitable for applications such as dewatering basements and draining ponds.



## ADDITIONAL IMAGES



## Product Overview

### Compact Submersible Performance

This submersible water transfer pump is engineered for continuous operation in demanding marine and freshwater environments. Its compact, lightweight design combines high delivery volume with a specialized motor cooling system and double mechanical seal for enhanced durability. Constructed with 304 stainless steel and corrosion-resistant materials, it provides a reliable solution for drainage, emergency pumping, and water circulation tasks.

## Technical Specifications

### Core Performance

**70 L/min**

Delivery Volume

**4 m**

Delivery Head

**45 W**

Motor Power

### Model Specifications

Feature	BL2524S	BL2512S
Voltage	DC 24V	DC 12V
Current	2.5A	5.4A

### Physical Dimensions

- Outlet Diameter: 25mm (1 inch)
- Weight: 1.3kg
- Operating Temperature: 0-60°C

## Features and Compliance

### Suitable Applications

- Bilge water discharge
- Boat emergency pumping
- Fish farm water exchange
- Deck washing
- Camping and car washing
- Freshwater preserve pumping

### Design Advantages

Continuous Operation, Double Mechanical Seal, Tool-Free Strainer, 304 Stainless Steel, Saltwater Resistant