

# Synthetic Fiber Endless Webbing Sling

This webbing sling is made from high-quality synthetic fiber using advanced weaving technology and various sewing methods. It has a load range from 0.5t to 50t and a safety factor of 4:1, 5:1, 6:1, 7:1, or 8:1, according to customer requirements.



## ADDITIONAL IMAGES



## Product Overview

### Professional Synthetic Lifting Solution

This high-tenacity polyester endless webbing sling is engineered for versatility and reliability in demanding industrial environments. Designed for superior flexibility, it conforms easily to various load shapes to ensure secure and balanced lifting operations. Manufactured in compliance with EN1492 standards, this sling is suitable for construction, manufacturing, and heavy-duty transportation sectors.

## Technical Specifications

### Ply Construction

- Single ply
- Double ply
- Four ply

### Standard Compliance

EN1492

Material	100% High Tenacity Polyester
Working Load Limit (WLL)	1 Ton to 12 Ton or higher
Width	25mm - 300mm
Available Safety Factors	4:1, 5:1, 6:1, 7:1, 8:1

## Design and Customization

### Lifting Eye Configurations

- Flat Eye
- Reversed Eye
- Folded Eye 1/2 Width from 1 Side
- Folded Eye 1/2 Width from 2 Sides
- Folded Eye 1/3 Width

### Customization

Available in lengths from 1m to 100m+, fully customizable to specific requirements.