

Thermal Ticket and Label Printer

This thermal printer is designed for efficient ticket and label printing. It features a user-friendly interface with a display screen and supports various roll configurations.



ADDITIONAL IMAGES



Overview

High-Performance Thermal Printing Solution

This advanced thermal ticket and label printer features a versatile dual-roll loading system, allowing for seamless switching between labels and wristbands. With a 300dpi resolution and a maximum print width of 108mm, it delivers high-precision output for one-dimensional and 2D barcodes, graphics, and text. Designed for efficiency, it includes an easy-access paper path to resolve jams quickly and an integrated LCD screen for real-time status monitoring.

Printing Performance

Resolution

300 dpi

Resolution

12 dots/mm

Dot Density

Print Speed

- Standard: 60mm/s
- Maximum: 5 ips

Print Width

10mm - 108mm

Connectivity & Software

Supported Barcodes

Type	Examples
Linear	Code 39, Code 128, UPC-A/E, EAN-13/8, Codabar, Interleaved 2 of 5
2-Dimensional	PDF-417, Maxicode, Data Matrix, QR code, Aztec

Connectivity

USB 2.0, Ethernet (RJ45), Wireless 802.11 b/g (Optional)

Physical Specifications

Dimensions & Weight

225 mm

Width

306 mm

Height

345 mm

Depth

3.32 kg

Weight

Operating Environment

Operating Conditions

Parameter	Range
Operating Temperature	4.4°C to 40°C
Storage Temperature	-40°C to 80°C
Operating Humidity	20% - 85% (non-condensing)

Electrical

Power Requirements

100-240VAC, 50-60Hz, 60 Watts

Compliance

Certifications

CE • RoHS • FCC