

Tractor-Mounted Rotary Tiller

This rotary tiller is soil-working equipment mounted to tractors with 12-160hp. It uses wide blades for effective stubble cleaning and simultaneous rotary tillage.



ADDITIONAL IMAGES



Overview



The rotary tiller features a robust frame, a central gearbox for power transmission, and a series of rotating blades designed for efficient soil cultivation.

Professional Soil Cultivation

This tractor-mounted rotary tiller is engineered for efficient soil preparation and cultivation across diverse agricultural environments. Designed for compatibility with tractors ranging from 12 to 160hp, it features wide, durable blades capable of simultaneous stubble cleaning and rotary tillage. Its robust construction ensures reliable performance in both dry and paddy field conditions, helping operators save significant time, labor, and operational costs.

Key Features

Key Features

Tractor-Mounted, Stubble Cleaning, Rotary Tillage, Dry Field Compatible, Paddy Field Compatible, Three-Point Linkage

Technical Specifications

Model Specifications

Model	Width (mm)	Blades (Qty)	Weight (kg)	Power (hp)
1GQN-100	1000	22	185	12-15
1GQN-115	1150	22	190	15-18
1GQN-120	1200	26	195	15-20
1GQN-125	1250	26	200	18-22
1GQN-140	1400	30	205	22-25
1GQN-150	1500	34	230	25-30
1GQN-160	1600	38	255	30-35
1GQN-180	1800	50	320	35-40

Operational Metrics

Working Depth (Dry Land)

8 mm

Min Depth

18 mm

Max Depth

Working Depth (Water/Paddy Land)

10 mm

Min Depth

20 mm

Max Depth

Compatibility

Linkage System

Standard three-point mounted