

# Twin Impeller Centrifugal Water Pump

These twin impeller centrifugal pumps are engineered for efficient water transfer and boosting. They are available in both single-phase and three-phase options.

TWIN IMPELLER CENTRIFUGAL PUMPS



Type	Nominal Power	Input Power	kVA	Capacity (m <sup>3</sup> /h - 10m <sup>3</sup> )						Inlet - Outlet	
				1.1	1.65	2.2	3.1	4.2	5.2		6.2
VB 150 / VB 150T	1.1	1.65	1.95	4.2	5.2	6.2	7.2	8.2	9.2	10.2	2" - 2"
VB 200 / VB 200T	1.65	2.2	2.6	5.2	6.2	7.2	8.2	9.2	10.2	11.2	
VB 300 / VB 300T	2.2	3.1	3.6	6.2	7.2	8.2	9.2	10.2	11.2	12.2	

## Overview

### High-Performance Twin Impeller Centrifugal Pumps

The VB series twin impeller centrifugal pumps are engineered for demanding water transfer and pressure-boosting applications. Built with robust construction, these units deliver high efficiency with a total head capacity of up to 66 meters. They are available in both single-phase and three-phase power configurations, providing versatile solutions for industrial and commercial fluid management.

## Performance

### Key Performance Metrics

**10.5 m<sup>3</sup>/h**

Max Capacity

**66 m**

Max Total Head

**2 inch**

Inlet/Outlet

## Technical Specifications

### Model Comparison Table

Model	Nominal Power (kW)	Input Power (kW)
VB 150 / 150T	1.1	1.85
VB 200 / 200T	1.65	2.22
VB 300 / 300T	2.2	3.1

### Configuration Options

Single-phase 230V, Three-phase 400V, 50Hz