

# Tyre Changer with Dual Helper Arms

This tyre changer features an operating platform with a distinctive shape. The dual helper arms control system ensures efficient and safe tyre removal and installation.



## Overview

### High-Efficiency Tyre Service Solution

This professional-grade tyre changer is equipped with advanced dual pneumatic helper arms, designed to streamline tyre removal and installation processes. With a robust 28-inch turntable and a powerful motor, it handles even low-profile tyres with precision and ease. Enhanced with features like a nylon pressing roller for rim protection and a quick air booster, this unit ensures damage-free operations while significantly increasing workshop productivity.

## Performance Metrics

### Key Performance Metrics

**2500 kg**

Bead Breaker Force

**28 inch**

Max Clamping Capacity

**8 bar**

Air Supply

## Technical Specifications

### Clamping Range

Clamping Type	Range
Outside Clamping	12"-25"
Inside Clamping	14"-28"

### Max Wheel Dimensions

- Max Diameter: 45 inch (1143mm)
- Max Width: 16 inch (406mm)

Power Requirements	110V, 220V, 400V
Motor Power Options	0.55kw, 0.75kw, 1.1kw

## Operational Features

### Advanced Capabilities

Dual Pneumatic Helper Arms • Rim Protection • Quick Air Booster • Low-Profile Tyre Compatible • Automatic Rocker Arms

## Physical Dimensions

Operating Noise Level	75 dB
Weight	276kg / 303kg