

Unicable SCR LNB with Legacy Ports

This Unicable SCR LNB is designed for satellite TV reception. It features both Unicable/SCR and Legacy outputs, allowing multiple receivers to connect using a single cable.



ADDITIONAL IMAGES



Product Overview

High-Performance Satellite Reception

This advanced LNB delivers excellent performance with a low noise figure and high gain, ensuring reliable signal reception across the full Ku-Band range. Featuring a versatile design, it includes one SCR (Single Cable Router) port and two legacy ports, which significantly simplifies the installation process. It is an ideal solution for both analog and digital satellite systems, providing flexibility for connecting multiple receivers efficiently.

Technical Specifications

Low Band Input Frequency	10.70 - 11.70 GHz
High Band Input Frequency	11.70 - 12.75 GHz
Low Band Output Frequency	950 - 1950 MHz
High Band Output Frequency	1100 - 2150 MHz
Noise Figure (Typ.)	0.3 dB
Image Rejection (Min.)	40 dB

Performance Metrics

L.O. Phase Noise

-75 dBc/Hz

1KHz

-80 dBc/Hz

10KHz

-90 dBc/Hz

100KHz

Connectivity

Key Features

- Supports digital and analog reception
- Single cable routing capability
- Weather-resistant construction
- Full Ku-Band coverage

Port Configuration

1x SCR Port, 2x Legacy Ports