

# Vortex Flowmeter with LCD Display

This flowmeter measures the flow of steam, air, gas, and water. It features an LCD display with 4-2mA output, flange connection, and SS304 material, with a diameter range of 25mm-300mm.

Livia Wang  
Tianjin Sure Instrument Science & Technology Co., Ltd  
URL: <http://www.suremeter.com>  
ADDRESS: No.12 Outer Ring Industrial Park, Tianjin, 300380, China  
Tel: (+86 22) 2373 2926; 2798 4345 ext 8401; Fax: 2798 4210  
Cell Phone: 0086 152 2207 0207  
E-mail: [livia@suremeter.com](mailto:livia@suremeter.com); [livia@sure365.com.cn](mailto:livia@sure365.com.cn); [wang.livia1020@hotmail.com](mailto:wang.livia1020@hotmail.com)  
SKYPE: wang.livia

## ADDITIONAL IMAGES



## Product Overview

### High-Precision Vortex Flowmeter

This industrial vortex flowmeter utilizes the von Kármán effect to provide accurate volumetric measurement for liquids, gases, and steam. Featuring a robust stainless steel construction, it is designed for demanding environments, process control, and HVAC applications. The integrated digital LCD display provides clear, real-time flow data for enhanced operational monitoring.

## Measurement Accuracy

### Accuracy Levels

Fluid Type	Accuracy
Liquid	±1.0%
Gas	±1.0%
Vapor Stream	±1.5%

## Technical Specifications

### Power Requirements

- Sensor: +12V DC (Optional: +24V DC)
- Transmitter: +24V DC
- Field Display: Integral 3.2V Lithium Battery or +24V DC

### Certifications & Ratings

IP65, ExdIIBT6, CE

## Operating Conditions

### Temperature Range

**-20**

Standard Minimum

**70**

Standard Maximum

**350**

Extended Maximum