

Wall-Mount Active Subwoofer with 8-Inch Driver and 120W Amplifier

This active subwoofer is designed for wall-mounted installations. It features an 8-inch driver and a built-in 120W RMS Class D amplifier for efficient low-frequency reproduction.



ADDITIONAL IMAGES



Overview

Professional Wall-Mount Subwoofer

This active subwoofer is engineered for professional audio installations where floor space is at a premium. Featuring a powerful 8-inch driver and a highly efficient 120W RMS Class D amplifier, it delivers precise, deep low-frequency reproduction. With versatile connectivity options including XLR, RCA, and Euroblock inputs, it integrates seamlessly into diverse commercial and home theater environments.

Performance

Rated Power (RMS)

120 W

RMS Power

300 W

Max Power

Frequency Response

70Hz - 120Hz

Maximum SPL

113dB / 122dB (Peak)

Audio Components

Driver Size

8 inch

Voice Coil

1.4 inch

Connectivity

Input Options

XLR, 1/4" Jack, RCA, Euroblock

Controls & Features

Available Controls

- Low-pass filter select switch
- Phase select switch
- Input level control
- Auto power (Stand-by)

Physical Specifications

Dimensions (WxDxH)	445 x 160 x 400 mm
Net Weight	8 kg

Logistics

Container Loading

Container Type	Quantity
20'	460
40'	960
40' HC	1120