

Waterproof Cable Gland for Double Locked Metal Cables

This waterproof joint is designed for double locked metal cables. It provides a secure and sealed connection, preventing moisture and contaminants from entering the cable termination point.




Product Overview

Professional Grade Cable Protection

This waterproof joint is engineered specifically for use with double-locked metal cables, ensuring a secure and reliable connection in challenging environments. The robust metallic construction provides excellent mechanical strength and environmental sealing, effectively preventing moisture and contaminants from reaching the termination point. Designed for professional industrial applications, its threaded interface allows for straightforward installation while maintaining a tight, high-integrity seal.

Technical Dimensions



Technical diagram illustrating internal components and key dimensions including thread length (GL).

Thread and Compatibility Specifications

Metric	PG	NPT	G	Cable Range (mm)	Thread Length (mm)	Wrench Size (mm)
M12x1.5	PG7	NPT1/4	G1/4	6.5-3	7	14
M14x1.5	-	-	-	8-4	7	18
M16x1.5	PG9	NPT3/8	G3/8	8-4	8	18
M18x1.5	PG11	-	-	10-5	8	20
M20x1.5	PG13.5	NPT1/2	G1/2	12-6	8	22
M22x1.5	PG16	-	-	14-10	8	24
M24x1.5	-	-	-	14-10	9	27
M25x1.5	PG19	-	-	14-10	9	27
M25x1.5	-	-	-	18-13	9	30
M27x1.5	-	-	-	18-13	9	30
M28x1.5	PG21	NPT3/4	G3/4	18-13	9	30
M30x1.5	-	-	-	18-13	9	32
M32x1.5	PG25	-	-	22-15	10	35

Features

Key Features

Waterproof, Double Locked Metal Cable Compatible, Threaded Installation, Mechanical Strength, Industrial Grade