

Waterproof Emergency Light Pushbutton Switch









This waterproof emergency light pushbutton switch is designed for industrial applications. It features robust construction for use in harsh environments.



ADDITIONAL IMAGES



Product Overview

 XDL21-CWC42	Illuminated Emergency stop Spring return with integral LED Latching	N/C 220~240V		 Red Φ 40 XDL21-CWC42	
	Spring return	N/O+N/C		 Red Φ 40 XDL21-CWCZ42	
	Latching			 Red Φ 40 XDL21-CWC45	
				 Red Φ 40 XDL21-CWCZ45	

Model equipped with integral LED for emergency status indication.

Industrial Emergency Control Solution

This waterproof emergency stop pushbutton switch is engineered for high-reliability control in demanding industrial environments. Featuring a robust zinc alloy and high-grade anti-flam plastic construction, it ensures durability and consistent performance. Designed for safety-critical applications, it includes a normally closed (N/C) contact for reliable breaking in emergency scenarios.

Technical Parameters



Specializing in production of buttons and indicators since 1997

High-durability mushroom-head emergency stop design.

Electrical Characteristics

660 V

Rated Insulation Voltage

10 A

Thermal Current

6 kV

Impulse Withstand

Operational Life

Component	Mechanical Cycles
Emergency Stop Button	300,000
Standard Button	3,000,000

Environmental and Standards

Environmental Rating

IP65 Protection

Certifications

CE, ISO 9001, RoHS, UL, IEC60947-5-1, GB/T14048.1

Operating Temperature Range

-5°C to +55°C

Physical Dimensions




Emergency stop
Turn to release

N/C



● Red $\Phi 40$ XDL21-CS542

● Red $\Phi 40$ XDL21-CT42



XDL21-CS542

Detailed dimensions for panel mounting.

Installation Details

- Mounting Diameter: 22mm
- Mushroom Head Diameter: 40mm
- Total Height: 49mm
- Max Panel Thickness: 5mm